

E-CLASS



PUMPER

Constructed with an aluminum extruded skeleton and plate paneling for maximum strength and rigidity.

PUMPER, RESCUE-PUMPER

- Custom designed extruded aluminum framework
- 3/16" and 1/8" body panel system for maximum strength
- Fully modular body with integrated sub-frame and 4-point, spring loaded mounting system
- Extended drop frame to chassis frame rails for maximum rear-of-body support
- Radius corners for the traditional American LaFrance styling
- Multiple body configurations available, including traditional pumper and Rescue-Pumper bodies
- Multiple pump configurations including American LaFrance pumps with capacities up to 2000 GPM
- Traditional aluminum pump house with choice of vinyl clad, anodized, or stainless steel panels
- All stainless steel hardware
- Superior service access for electrical components, harnesses, fuel tank, and plumbing





Hose loads, equipment storage and warning lights tailored to order



Custom options abound to provide unique or individual requirements



Extrusion framework design welds joints inside and out



Body mounts are strategically located based on configuration



Spring loaded 4-point body mounting design reduces road shock transfer



Body frame with integral tank support provides lasting strength

E-CLASS

These are the typical specifications for the American LaFrance E-Class Pumper Bodies:

CHASSIS: American LaFrance custom chassis, Freightliner M2, or Sterling Acterra.

CONSTRUCTION: Fully welded extruded aluminum bodies with custom designed extrusions and body paneling system of 1/8" and 3/16" aluminum sheet.

MOUNT SYSTEM: Four point spring loaded mounting with extended drop frame off chassis rails at rear of body.

BODY STYLES: Multiple body configurations available including traditional high/low pumpers and three to five compartment (per side) rescue pumpers.

WATER CAPACITY: Polypropylene tanks from 500 to 1250 gal.

PUMP HOUSE: Traditional aluminum pump house and overlap panel with optional painted frame/inset panel upgrade in both side mount and top mount configurations.

PUMPS: Multiple pumps available including American LaFrance Twin Flow™ split-shaft pumps with capacities from 1000 to 2000 GPM.

FOAM SYSTEMS: Single or dual tank systems available with foam cells integral to the water tank.

DOORS: Roll-up doors standard with optional hinged overlap doors (with full perimeter gasketing).

LADDER STORAGE: Standard side wall storage brackets with optional internal ladder storage or optional single and dual overhead electric/hydraulic racks for maximum compartment availability.

GENERATORS: PTO driven hydraulic generators with capacities up to 15 KW or compartment mounted gasoline generators with capacities up to 5 KW. Additional options available upon request.

SCENE LIGHTING: Multiple truck mounted scene lighting available, including folding light towers, telescoping lights on the back of cab and body, or removable tripod lighting in 500W, 1000W, or 1500W lighthead.

For your nearest American LaFrance dealer, call 1-888-253-8725.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. American LaFrance is ISO 9001 and 14001 certified. ©2005 American LaFrance, LLC. NOTE: American LaFrance is a registered ISO 9001 and 14001 manufacturer for Class 7 and Class 8 fire apparatus.

